



HIGH TENSION WILDLIFE FENCE

(For PAs & Other Wildlife Areas)
GOOD FENCES MAKE GOOD NEIGHBOURS



Wildlife & Forestry Services

C13/21, Mahakal Vanijya Kendra

Ujjain 456010

9425916822, 9644080679

mail@wfsindia.co.in

wildforestindia@gmail.com

FIXED KNOT FENCE

ANATOMY & SPECIFICATIONS

FK-16-180-15 (6 Feet Height)

FK: Fixed Knot fence

16: 16 Number of horizontal wires

180: 180cm Height of Fence (1.80 meters)

15: 15 cm distance between two vertical wires (stay wires)

Spacing between horizontal lines from bottom to top

Spacing: 3.50: 3.50: 3.50: 3.50: 3.50: 4.00: 4.00: 5.00: 5.00: 5.00: 5.50: 5.50: 6.00: 6.00: 7.00

(Total 70.5" Inches)

Top & 4th Wire (Horizontal Wire): Diameter 2.75 MM +/- 0.03 MM

Strength of wire: 1150 to 1300 Mpa (Megapascal units of strength)

Coating: Minimum 250 Gsm. (Gram per meter square) Bezinal 2000 Class W10.
(Bezinal 2000 coating is Aluminium Zinc coating)

Bottom 3 Line Wire (Horizontal Wire): Diameter 2.44 MM +/- 0.03 MM

Strength of wire: 1150 to 1300 Mpa (Megapascal units of strength)

Coating: Minimum 240 Gsm. (Gram per meter square) Bezinal 2000 Class W10.
(Bezinal 2000 coating is Aluminium Zinc coating)

Remaining 11 Line Wire (Horizontal Wire): Diameter 2.44 MM +/- 0.03 MM

Strength of wire: 1150 to 1300 Mpa (Megapascal units of strength)

Coating: Minimum 240 Gsm. (Gram per meter square) Bezinal 2000 Class W10.
(Bezinal 2000 coating is Aluminium Zinc coating)

(Bezinal 2000 coating is Aluminium Zinc coating)

Knots: Top 11 knots Wire diameter 2.24 MM +/- 0.03 MM

Strength of wire: 380 to 550 Mpa (Megapascal units of strength)

Coating: Minimum 220 Gsm. (Gram per meter square) Bezinal 2000 Class W10.
(Bezinal 2000 coating is Aluminium Zinc coating)

Stay Wire (Verticle Wire): Wire diameter 2.44 MM +/- 0.03 MM

Strength of wire: 1150 to 1300 (Megapascal units of strength)

Coating: Minimum 240 Gsm. (Gram per meter square) Bezinal 2000 Class W10.
(Bezinal 2000 coating is Aluminium Zinc coating)

Coil Weight: Approximate 74 kgs

Coil Length: 50 meters (164' Ft)

Coil Height: 1.8 Meters (72' Inch/6 Ft)

Main Post : Hot dipped galvanised (60x3x2750 MM with PVC cap) placed at a distance of 47 meters, grouted with concrete.

Support Post : Hot dipped galvanised (33x3x2750 MM with brace band 60 mm, Hex nut M8x25MM), 2 per main post and 1 per corner post, grouted with concrete.

Intermediate Post: Hot dipped galvanised T angle (25x25x2750 MM) placed at a distance of every 6 meters excluding main posts and corner posts.

Extension: Scope for extending the height of the fence by 1 feet by adding extra fabric or wires at the top.

Cost: Kindly call for enquiry

Includes: Complete material and installation

Excludes: Fence line clearing

Payment Terms: 100% advance against purchase order